

## Pellet Air

### TECHNICAL DATA

Thermic Power (at min-at max)	kW	2,4 - 9,1
Introduced thermal power (at max)	kW	10,3
Water useful power (at min-at max)	kW	-
Seasonal energy efficiency	$\eta_s$ [%]	85
Useful efficiency (at min-at max)	%	92,9 - 88,7
Heating surface (at min-at max)	m <sup>2</sup>	25,3 - 96,1
CO <sub>2</sub> (min-max)	%	8,5 - 13,9
Emissions CO (13% O <sub>2</sub> ) (at min-at max)	mg/Nm <sup>3</sup>	274 - 63
Emissions OGC (13%O <sub>2</sub> ) (at min-at max)	mg/Nm <sup>3</sup>	3.9- 2.1
Emissions NOX (13% O <sub>2</sub> ) (at min-at max)	mg/Nm <sup>3</sup>	104 - 139
Dust content at 13% O <sub>2</sub> (at min-at max)	mg/Nm <sup>3</sup>	19.3 - 12.1
Combustible Pellet	mm	ø6 L31-40
Boiler capacity (H <sub>2</sub> O)	l	-
Hopper capacity	kg	17
Hourly consumption (at min-at max)	kg/h	0,53 - 2,12
Autonomy (at min-at max)	h	32 - 8
Supply and frequency	V-Hz	230-50
Ignition electrical absorption (at max)	W	346
Operating electrical absorption (at max)	W	77
Chimney flue depression (at min-at max)	Pa	2 - 11.6
Mass of smoke (at min-at max)	g/sec	2,2 - 5,0
Exhaust fumes temperature (at min-at max)	°C	0 - 0
Distance from material comb. (back/side/under)	mm	200 / 200 / 0
Distance to material comb. (front/top)	mm	1000
Exhaust fumes outlet (A)	Ø mm	80
Combustion air inlet (B)	Ø mm	130
Ducting outlet (C)	Ø mm	0
Ductable up to	m	-

### PLUS



Integrated concentric outlet (80-130 mm)



Sealed Chamber



Magic Glass



Cast iron burning pot



Comfort mode - Maximum silence



Integrated Wi-Fi and Bluetooth



Connection to the external therm.



Weekly programming



Upper exhaust

### AVAILABLE FINISHES

7019018		Steel Anthracite	EAN 8053859010777
7019019		Steel White	EAN 8053859010784
7019021		Steel Titanium	EAN 8053859010807

### CERTIFICATIONS


European standards  
Art. 15A B-VG 2015  
BlmSchV 2015  
Regensburg  
München  
Stuttgart  
Aachen



EN 14785:2006



### STOVE PACKAGE



L (cm)	H (cm)	P (cm)
80	130	68
Volume (m <sup>3</sup> )	0,71	
Gross weight (kg)	99	
Net weight (kg)	88	

### STORAGE



N° (max)
1

### TRANSPORT



60 pz