



Pellet Air Plus

TECHNICAL DATA

| | | |
|---|--------------------|---------------|
| Thermic Power (at min-at max) | kW | 3,7 - 12,0 |
| Introduced thermal power (at max) | kW | 13,5 |
| Water useful power (at min-at max) | kW | - |
| Seasonal energy efficiency | η_s [%] | 84 |
| Useful efficiency (at min-at max) | % | 90,0 - 89,2 |
| Heating surface (at min-at max) | m ² | 39,1 - 126,7 |
| CO ₂ (min-max) | % | 5,0- 11,9 |
| Emissions CO (13% O ₂) (at min-at max) | mg/Nm ³ | 140 - 125 |
| Emissions OGC (13%O ₂) (at min-at max) | mg/Nm ³ | 10- 2 |
| Emissions NOX (13% O ₂) (at min-at max) | mg/Nm ³ | 120 - 99 |
| Dust content at 13% O ₂ (at min-at max) | mg/Nm ³ | 17 - 15 |
| Combustible Pellet | mm | ø6 L31-40 |
| Boiler capacity (H ₂ O) | l | - |
| Hopper capacity | kg | 23 |
| Hourly consumption (at min-at max) | kg/h | 0,90 - 2,80 |
| Autonomy (at min-at max) | h | 26 - 8 |
| Supply and frequency | V-Hz | 230-50 |
| Ignition electrical absorption (at max) | W | 360 |
| Operating electrical absorption (at max) | W | 155 |
| Chimney flue depression (at min-at max) | Pa | 2 - 12 |
| Mass of smoke (at min-at max) | g/sec | 5,7 - 8,8 |
| Exhaust fumes temperature (at min-at max) | °C | 107 - 216 |
| Distance from material comb. (back/side/under) | mm | 200 / 300 / 0 |
| Distance to material comb. (front/top) | mm | 1000 / 750 |
| Exhaust fumes outlet (A) | Ø mm | 80 |
| Combustion air inlet (B) | Ø mm | 60 |
| Ducting outlet (C) | Ø mm | 80 |
| Ductable up to | m | 8 |

PLUS

- Integrated Wi-Fi and Bluetooth
- Cast iron door
- Sealed Chamber
- Cast iron burning pot
- Cast iron inner
- Duction with 2 independ. motors
- Comfort mode - Maximum silence
- Connection to the external therm.
- Weekly programming

AVAILABLE FINISHES

| | | | |
|---------|--|--------------------|-------------------|
| 7023084 | | Steel White | EAN 8053859020271 |
| 7023085 | | Steel Red Bordeaux | EAN 8053859020288 |
| 7023086 | | Steel Anthracite | EAN 8053859020295 |
| 7023087 | | Steel Light Bronze | EAN 8053859020301 |
| 7023088 | | Steel Titanium | EAN 8053859020318 |
| 7023089 | | Stone Serpetino | EAN 8053859020325 |

OPTIONAL

| | | |
|---------|---------------------|-------------------|
| 5020001 | 90° CURVE KIT SMOKE | EAN 8053859012474 |
|---------|---------------------|-------------------|

CERTIFICATIONS

European standards
Art. 15A B-VG 2015
BImSchV 2015
Regensburg
München
Stuttgart
Aachen

EN 14785:2006



STOVE PACKAGE

| | | | |
|--|--------------------------|--------|--------|
| | L (cm) | H (cm) | P (cm) |
| | 80 | 130 | 103 |
| | Volume (m ³) | 1,07 | |
| | Gross weight (kg) | 177 | |
| | Net weight (kg) | 161 | |

STORAGE

| | |
|--|----------|
| | N° (max) |
| | 1 |
| | MAX 1 |

TRANSPORT

| |
|-------|
| |
| 39 pz |