

Pellet Air Plus

TECHNICAL DATA

Thermic Power (at min-at max)	kW	3,3 - 8,5
Introduced thermal power (at max)	kW	9,9
Water useful power (at min-at max)	kW	-
Seasonal energy efficiency	ηs [%]	86
Useful efficiency (at min-at max)	%	89,0 - 89,0
Heating surface (at min-at max)	m ²	34,2 - 88,2
CO ₂ (min-max)	%	5,9 - 12,0
Emissions CO (13% O ₂) (at min-at max)	mg/Nm ³	140 - 125
Emissions OGC (13%O ₂) (at min-at max)	mg/Nm ³	3 - 7
Emissions NOX (13% O ₂) (at min-at max)	mg/Nm ³	133 - 100
Dust content at 13% O ₂ (at min-at max)	mg/Nm ³	15 - 15
Combustible Pellet	mm	ø6 L31-40
Boiler capacity (H ₂ O)	l	-
Hopper capacity	kg	15
Hourly consumption (at min-at max)	kg/h	0,70 - 2,00
Autonomy (at min-at max)	h	21 - 8
Supply and frequency	V-Hz	230-50
Ignition electrical absorption (at max)	W	300
Operating electrical absorption (at max)	W	100
Chimney flue depression (at min-at max)	Pa	2 - 11
Mass of smoke (at min-at max)	g/sec	3,5 - 4,8
Exhaust fumes temperature (at min-at max)	°C	164 - 286
Distance from material comb. (back/side/under)	mm	200 / 200 / 0
Distance to material comb. (front/top)	mm	1000 / 750
Exhaust fumes outlet (A)	Ø mm	80
Combustion air inlet (B)	Ø mm	60
Ducting outlet (C)	Ø mm	80
Ductable up to	m	6

PLUS



AVAILABLE FINISHES

7023043	Steel Light Bronze	EAN 8053859019336
7023044	Steel Titanium	EAN 8053859019343
7023045	Stone Nero Greco	EAN 8053859019350
7023046	Stone Ossido Bruno	EAN 8053859019367
7023047	Glass Black	EAN 8053859019374

OPTIONAL

5023001	UPPER EXHAUST + CONCENT KIT	EAN 8053859019473
---------	-----------------------------	-------------------

CERTIFICATIONS

European standards
Art. 15A B-VG 2015
BImSchV 2015
Regensburg
München
Stuttgart
Aachen


EN 14785:2006
CE



STOVE PACKAGE

	L (cm)	H (cm)	P (cm)
	80	131	103
	Volume (m ³)	1,08	
	Gross weight (kg)	136	
	Net weight (kg)	126	

STORAGE



TRANSPORT

