

Wood

TECHNICAL DATA

Thermic Power (at min-at max)	kW	0,0 - 7,5
Introduced thermal power (at max)	kW	9,4
Water useful power (at min-at max)	kW	-
Seasonal energy efficiency	ηs [%]	76
Useful efficiency (at min-at max)	%	0,0 - 85,5
Heating surface (at min-at max)	m ²	0,0 - 79,2
CO ₂ (min-max)	%	0,0 - 9,6
Emissions CO (13% O ₂) (at min-at max)	mg/Nm ³	0 - 1167
Emissions OGC (13%O ₂) (at min-at max)	mg/Nm ³	0 - 69
Emissions NOX (13% O ₂) (at min-at max)	mg/Nm ³	0 - 85
Dust content at 13% O ₂ (at min-at max)	mg/Nm ³	0 - 20
Combustible Legna	mm	max L 330
Boiler capacity (H ₂ O)	l	-
Hopper capacity	kg	-
Hourly consumption (at min-at max)	kg/h	0,00 - 2,10
Autonomy (at min-at max)	h	0 - 0
Supply and frequency	V-Hz	
Ignition electrical absorption (at max)	W	-
Operating electrical absorption (at max)	W	-
Chimney flue depression (at min-at max)	Pa	- - 12
Mass of smoke (at min-at max)	g/sec	0,0 - 7,1
Exhaust fumes temperature (at min-at max)	°C	0 - 215
Distance from material comb. (back/side/under)	mm	40 / 2,5 / 0
Distance to material comb. (front/top)	mm	1000 / 750
Exhaust fumes outlet (A)	Ø mm	140
Combustion air inlet (B)	Ø mm	80
Ducting outlet (C)	Ø mm	0
Ductable up to	m	-

PLUS



Cast iron door



Cooking



View on the Oven



Refractory stone



Upper and back exhaust



Built-in

AVAILABLE FINISHES

71220034		Steel Anthracite	EAN 8053859016557
71220035		Steel White	EAN 8053859016564
71220036		Steel Red Bordeaux	EAN 8053859016571

OPTIONAL

5020007	STAINLESS STEEL PLINTH	EAN 8053859012610
5020010	INOX H4 UPSTAND SMART 80	EAN 8053859012641
5020011	INOX H6 UPSTAND SMART 80	EAN 8053859012658
5020005	FEET SMART 60/80	EAN 8053859012597
5021005	CONNECTOR PIPE 140-150MM	EAN 8053859014256
5013003	TOP	EAN 8033123613361

CERTIFICATIONS

European standards
BImSchV 2015
Regensburg
München
Stuttgart
Aachen




EN 12815:2001/
A1:2004/AC:2007



A+

STOVE PACKAGE



L (cm)	H (cm)	P (cm)
80	102	98
Volume (m ³)	0,80	
Gross weight (kg)	166	
Net weight (kg)	152	

STORAGE



N° (max)
1

TRANSPORT



39 pz