

## Wood Air

### TECHNICAL DATA

Thermic Power (at min-at max)	kW	0,0 - 7,0
Introduced thermal power (at max)	kW	8,4
Water useful power (at min-at max)	kW	-
Seasonal energy efficiency	ηs [%]	74
Useful efficiency (at min-at max)	%	0,0 - 84,0
Heating surface (at min-at max)	m <sup>2</sup>	0,0 - 72,6
CO <sub>2</sub> (min-max)	%	0,0 - 8,8
Emissions CO (13% O <sub>2</sub> ) (at min-at max)	mg/Nm <sup>3</sup>	0 - 1250
Emissions OGC (13%O <sub>2</sub> ) (at min-at max)	mg/Nm <sup>3</sup>	0 - 60
Emissions NOX (13% O <sub>2</sub> ) (at min-at max)	mg/Nm <sup>3</sup>	0 - 110
Dust content at 13% O <sub>2</sub> (at min-at max)	mg/Nm <sup>3</sup>	0 - 30
Combustible Legna	mm	max L 500
Boiler capacity (H <sub>2</sub> O)	l	-
Hopper capacity	kg	-
Hourly consumption (at min-at max)	kg/h	0,00 - 1,90
Autonomy (at min-at max)	h	0 - 0
Supply and frequency	V-Hz	230-50
Ignition electrical absorption (at max)	W	-
Operating electrical absorption (at max)	W	20
Chimney flue depression (at min-at max)	Pa	-- 12
Mass of smoke (at min-at max)	g/sec	0,0 - 6,7
Exhaust fumes temperature (at min-at max)	°C	0 - 211
Distance from material comb. (back/side/under)	mm	250 / 320 / 130
Distance to material comb. (front/top)	mm	1100 / 750
Exhaust fumes outlet (A)	Ø mm	150
Combustion air inlet (B)	Ø mm	80
Ducting outlet (C)	Ø mm	0
Ductable up to	m	-

### PLUS

- Anti-smoke valve
- Bûches 50 cm
- Sealed Chamber
- Cast iron door
- Refractory stone
- Ventilation
- Upper exhaust

### AVAILABLE FINISHES


7024015	● Cast Iron	EAN 8053859020714
---------	-------------	-------------------

### OPTIONAL

5024011	SERPENTINO STONE TOP KIT	EAN 8053859021001
---------	--------------------------	-------------------

### CERTIFICATIONS

European standards  
Art. 15A B-VG 2015  
BImSchV 2015  
Regensburg  
München  
Stuttgart  
Aachen



EN 13240  
CE

### STOVE PACKAGE

	L (cm)	H (cm)	P (cm)
	80	96	71
	Volume (m <sup>3</sup> )	0,55	
	Gross weight (kg)	150	
	Net weight (kg)	140	

### STORAGE

	N° (max)
	2
MAX 2	
1	

### TRANSPORT

57 pz