

Pellet Air Plus

TECHNICAL DATA

Thermic Power (at min-at max)	kW	2,5 - 8,5
Introduced thermal power (at max)	kW	9,7
Seasonal energy efficiency	η_s [%]	83
Useful efficiency (at min-at max)	%	90 - 87
Heating surface (at min-at max)	m ²	26 - 88
CO ₂ (min-max)	%	6,3 - 12,0
Emissions CO (13% O ₂) (at min-at max)	mg/Nm ³	297 - 160
Emissions OGC (13%O ₂) (at min-at max)	mg/Nm ³	5- 3
Emissions NOX (13% O ₂) (at min-at max)	mg/Nm ³	120 - 140
Dust content at 13% O ₂ (at min-at max)	mg/Nm ³	20 - 15
Combustible Pellet	mm	Ø6 L3÷40
Hopper capacity	kg	17
Hourly consumption (at min-at max)	kg/h	0,6 - 2,1
Autonomy (at min-at max)	h	28 - 8
Supply and frequency	V-Hz	230-50
Ignition electrical absorption (at max)	W	340
Operating electrical absorption (at max)	W	106
Chimney flue depression (at min-at max)	Pa	2 - 12
Mass of smoke (at min-at max)	g/sec	3,1 - 6,0
Exhaust fumes temperature (at min-at max)	°C	125 - 229
Distance from material comb. (back/side/under)	mm	200 / 300 / 15
Distance to material comb. (front/top)	mm	1000 / 750
Exhaust fumes outlet (A)	Ø mm	80
Combustion air inlet (B)	Ø mm	50
Ducting outlet (C)	Ø mm	80
Ductable up to	m	7

PLUS



Concentric flue kit (optional)



Sealed Chamber



Cast iron burning pot



Duction with 1 independent motor



Comfort mode - Maximum silence



Integrated Wi-Fi and Bluetooth



Connection to the external therm.



Weekly programming



Back exhaust

AVAILABLE FINISHES

7022090		Steel White	EAN 8053859015802
7022092		Steel Anthracite	EAN 8053859015826
7022093		Steel Light Bronze	EAN 8053859015833
7022094		Steel Titanium	EAN 8053859015840

OPTIONAL

5020003	UPPER DUCTING KIT	EAN 8053859012573
5022001	UPPER EXHAUST KIT	EAN 8053859015536
5022003	UPPER EXHAUST + CONCENT KIT	EAN 8053859015550


CERTIFICATIONS

European standards
Art. 15A B-VG 2015
BlmSchV 2015
Regensburg
München
Stuttgart
Aachen

EN 14785:2006



STOVE PACKAGE



L (cm)	H (cm)	P (cm)
80	118	61
Volume (m ³)	0,58	
Gross weight (kg)	97	
Net weight (kg)	87	

STORAGE




MAX 2

1

N° (max)
2

TRANSPORT



66 pz