


Certificazioni



Plus



Dati tecnici

Modello	Profondità (mm)	Altezza (mm)	Larghezza (mm)	Interasse (mm)	Peso (kg)	Capacità (lt)	Δt=50°C (kcal/h)	Δt=50°C (Watt)	Δt=40°C (Watt)	Δt=30°C (Watt)	Δt=20°C (Watt)	Esponente	Funz. misto (Watt)
01													
818 17 tubi 1 intervallo	30,0	818	450	406	5,10	3,80	309,0	360,0	273,0	192,0	116,0	1,231	300
818 17 tubi 1 intervallo	30,0	818	500	456	5,50	4,10	338,0	393,0	299,0	210,0	128,0	1,228	400
818 17 tubi 1 intervallo	30,0	818	550	506	5,90	4,40	367,0	427,0	325,0	228,0	139,0	1,225	400
818 17 tubi 1 intervallo	30,0	818	600	556	6,30	4,70	396,0	460,0	351,0	247,0	150,0	1,222	400
818 17 tubi 1 intervallo	30,0	818	750	706	9,90	5,30	483,0	561,0	428,0	302,0	185,0	1,213	400
1248 25 tubi 2 intervalli	30,0	1248	450	406	7,50	5,70	462,0	538,0	408,0	286,0	173,0	1,235	400
1248 25 tubi 2 intervalli	30,0	1248	500	456	8,10	6,10	506,0	588,0	447,0	313,0	190,0	1,234	400
1248 25 tubi 2 intervalli	30,0	1248	550	506	8,70	6,50	549,0	638,0	485,0	340,0	206,0	1,232	400
1248 25 tubi 2 intervalli	30,0	1248	600	556	9,30	7,00	592,0	689,0	523,0	367,0	223,0	1,230	700
1248 25 tubi 2 intervalli	30,0	1248	750	706	14,60	7,90	722,0	840,0	639,0	449,0	274,0	1,224	700
1592 31 tubi 3 intervalli	30,0	1592	450	406	9,40	7,10	604,0	703,0	530,0	369,0	221,0	1,263	700
1592 31 tubi 3 intervalli	30,0	1592	500	456	10,10	7,60	655,0	762,0	575,0	401,0	241,0	1,258	700
1592 31 tubi 3 intervalli	30,0	1592	550	506	10,90	8,20	706,0	821,0	621,0	433,0	261,0	1,252	700
1592 31 tubi 3 intervalli	30,0	1592	600	556	11,70	8,70	757,0	880,0	666,0	466,0	281,0	1,246	700
1592 31 tubi 3 intervalli	30,0	1592	750	706	18,20	9,80	909,0	1.057,0	803,0	564,0	343,0	1,228	1000